

ACRYPUTTY PLUS

Premium Quality Acrylic Putty

DESCRIPTION AND USES

- **Acryputty Plus** is an Acrylic polymer water-based high-quality putty.
- For interior and exterior use.
- Conforms to Egyptian Standard Specification 6623/2008
- Ideal for smoothening and leveling of interior walls & ceilings prior to using emulsion or oil based paints.
- Specially formulated to give excellent filling and workability.
- It has strong adhesion and has water-beading effect.
- It is water-based environmentally friendly product.

PRODUCT PROPERTIES

Finish	Matt / Flat
Colour	White
Density at 25°C	Approx. 1.83 Kg / Ltr.
Solid Content by Volume (%)	54.5 ± 2
VOC – Volatile Organic Compound	0 (g/l) "according to EU Regulation"
Diluents / Thinner	Dilution is not required
Drying Time at 25°C & Relative Humidity 50%	• Touch Dry: 30 – 60 min • Recoat: 3 – 4 hours • Full Dry: 12 hours

PACKAGING

Refer to company price list or contact the local representative.

INSTRUCTIONS FOR USE

1. Surface preparation:

- Surface must be clean, free from oil, grease, dirt, chalk, loose paint and any other foreign materials.
- Old painted surfaces should be cleaned from loose paint and other materials that can affect adhesion.
- Absorbent substrates should be moistened with water and sealed.
- Concrete, plaster and masonry surfaces should be fully cured before applying putty (at least 4 weeks for concrete and 10 days for plaster and masonry).

2. Recommended Application System:

- Use one of the suitable primers from **SCIB** for priming purposes and to seal porous surfaces.
- **Acryputty Plus** is applied with no further additions / dilution.
- Surface must be completely dry between successive coats (minimum 2 hours drying time depending on temperature and humidity).
- In case more than 3 mm layer thickness is required, it is advisable to apply in more than one layer with 24 hours interval (or less depending on temperature) between each layer.
- Substrate should be sanded lightly between two coats.
- Application of one of the suitable primers from **SCIB** after putty application helps to increase spreading and adhesion of finish paint.

APPLICATION TOOLS



STORAGE & SHELF LIFE

18 months in original tightly closed containers away from direct sunlight and excessive heat.

THEORETICAL COVERAGE

0.5 – 1 kg / m²

Practical coverage varies depending on surface porosity, application method, DFT & losses.

SAFETY PRECAUTIONS

- Please refer to material safety data sheet (MSDS) before using the product.
- Please revert to technical office for application advice. For alternative systems may be specified, depending on area of use.

معجون أكرليك عالي الجودة

الوصف والاستخدامات

- **أكري باتي بلس** معجون مائي عالي الجودة بأساس أكريليك بوليمير.
- للإستخدام الداخلي و الخارجي.
- المنتج مطابق للمواصفة القياسية المصرية (٢٠٠٨/٦٦٢٣).
- يستخدم لتنعيم و تسوية الحوائط و الأسقف قبل إستخدام الدهانات البلاستيك و اللاكيئات.
- مصمم خصيصا ليعطي قدرة تخبئة عالية وقابلية عالية للتشغيل.
- يتميز بالقدرة العالية للألتصاق وقدرة عالية على عدم الإمتصاص.
- منتج بأساس مائي وصديق للبيئة.

خصائص المنتج

الشكل النهائي	مط / ناعم
اللون	أبيض
الكثافة عند درجة ٢٥ °م	تقريباً ١,٨٣ كجم / لتر
محتوى الصلب بالحجم	٥٤,٥ ± ٣
المواد العضوية المتطايرة (VOC (g/Ltr	٠ جم/لتر طبقا للمواصفات الأوروبية
المذيب / المخفف	جاهز للاستخدام بدون تخفيف
زمن الجفاف عند درجة ٢٥ ° مئوية ونسبة الرطوبة ٥٠٪	<ul style="list-style-type: none"> • جفاف مبدئي : ٣٠ - ٦٠ دقيقة • وجه ثلاني : ٣ - ٤ ساعات • وجه نهائي : ١٢ ساعة

العبوات المتوفرة

لمزيد من المعلومات يرجى الرجوع إلى قائمة أسعار الشركة أو أقرب وكيل.

تعليمات الاستخدام

١. تجهيز السطح :

- يراعى نظافة السطح المراد دهانه وخلوه من الزيوت والشحوم والأتربة كما يراعى تماسك السطح وعدم وجود أجزاء منفصلة.
- في حالة تطبيق المنتج على أسطح مدهونة مسبقاً يراعى نظافة السطح وإزالة طبقة الدهانات غير المتماسكة وخلو السطح من أي مواد غريبة تؤثر على قوة الالتصاق.
- يراعى معالجة الأسطح المسامية باستخدام السيلر المناسب قبل تطبيق المعجون.
- يراعى جفاف الأسطح الأسمنية والجسبية و المجارة قبل تطبيق المعجون (على الأقل ٤ اسابيع للخرسانة و ١٠ أيام للمجارة).

٢. خطوات التنفيذ المقترحة :

- يستخدم برايرمر مناسب من برايرمرات **سكيب** لغلق المسام قبل تطبيق المعجون .
- يتم تطبيق **معجون أكري بتي بلس** دون أي إضافات أو تخفيف.
- يجب ترك زمن كافى للجفاف بين الطبقات المتتالية (ساعاتان على الأقل حسب درجة الحرارة و الرطوبة) في حالة عمل سمك من المعجون يزيد عن ٣ مم ينصح بعمل اكثر من طبقة مع فاصل زمنى ٢٤ ساعة بين كل طبقة (يمكن أن تقل الفترة الزمنية حسب درجة الحرارة المحيطة).
- براعى عمل صنفرة خفيفة لسطح المعجون قبل تطبيق الطبقات التالية.
- دهان طبقة **السيلاز/البرايرمر** المناسب من **سكيب** فوق المعجون وقيل الدهان تساعد على تحسين معدل الاستهلاك للدهانات و التصاقها بالسطح.

أدوات التطبيق



التخزين ومدة الصلاحية

١٨ شهر في العبوة الأصلية محكمة الغلق و بعيدا
عن أشعة الشمس المباشرة و الحرارة.

معدل الاستهلاك الاسترشادي

٠,٥ - ١ كجم/م^٢
التغطية الفعلية تختلف على حسب مسام السطح، طريقة التطبيق، سمك طبقة الدهان الفعلية ونسبة الفاقد.

تعليمات الأمن و السلامة

- يرجى الرجوع إلى نشره السلامة الخاصة بالمنتج (MSDS) قبل الاستخدام.
- يرجى الرجوع إلى المكتب الفني لمزيد من الاستشارات بخصوص التطبيق.
- يمكن توصف أنظمة دهان بدلة وذلك بناء على مناطق الاستخدام.

ان المعلومات الواردة فى هذه الصفحة هى افضل ما لدينا من المعرفة القائمة على التجارب العملية والخبرة العملية. وبما ان المنتج يستعمل غالبا تحت ظروف خارج نطاق مراقبتنا، فانا لا نستطيع ضمان أى شئ سوى نوعية المنتج نفسه ونحتفظ بحق تغيير البيانات المعطاه دون اشعار مسبق. هذه المواصفات الفنية تلغى أى مواصفات سابقا. لمزيد من الاستفسار يرجى مراجعة المكتب الفنى.

أب، ٢٠٢٤